

UP TO  
**55%**  
**ENERGY SAVINGS**  
400–1200W HID replacement

**SuperNova™**

High powered multiple optic floodlight with back spill light control

The NEW SuperNova™ LED floodlight is a high powered solution perfect for any industrial estate, mid-sized sporting field or court.

Improve area safety and visual comfort by delivering quality area light using tailored asymmetric optics.

Minimise light pollution and spill into nearby premises using full cut off optics, glare control and optional backward spill guard.

Achieve a perfect balance between superior optical performance and energy consumption.

## CONTRACTOR BENEFITS

- **Easy installation** using a versatile bracket
- **High luminaire efficacy** of greater than 140 Lm/W
- **IP66** - Ingress protection
- **IK10** - Highest level of impact resistance

## APPLICATIONS



INDUSTRIAL  
ESTATES



BUILDING  
PERIMETERS



SPORTS  
FIELD



SPORTS  
COURT



OUTDOOR  
CAR PARKS



LOADING  
DOCKS

## FEATURES



SAFETY  
COMPLIANCE



EASY  
INSTALL



DIRECTIONAL  
LIGHT THROW



INGRESS  
PROTECTION



IMPACT  
RATING



YEAR  
WARRANTY

**enLighten**

## PRODUCT RANGE


Model #	Rated Power (W)	Lumen Output (lm)	Dimensions (mm)	Weight (kg)
SFL-180-40K-Lx	180	25,200	685 x 362 x 94	9.3
SFL-240-40K-Lx	240	33,600	685 x 362 x 94	9.3
SFL-300-40K-Lx	300	42,000	685 x 362 x 94	9.9
SFL-450-40K-Lx	450	63,000	740 x 658 x 104	19.9
SFL-600-40K-Lx	600	84,000	740 x 658 x 104	21.4

\* x represents optics option and can be 1-9 depending upon the type of optic as shown on photometrics. The lensing option will determine lumen output. Add -BSG to the item number for the back spill guard (available for lens options L2, L3, L4, L5, L6).


## CLIENT BENEFITS

- **Multiple optic floodlight**
- **Directional light throw** - Tailored asymmetrical lenses
- **Optional back spill guard** to control light trespass
- **Long lasting Seoul Semiconductor LEDs** with over 130,000 hours of operating life @ L70
- **Lightning surge protection** - 10 kV


## PHOTOMETRICS




L1 Lens




L2 Lens




L3 Lens




L4 Lens




L5 Lens




L6 Lens



L7 Lens




L8 Lens



L9 Lens

## DIMENSIONS



## TECHNICAL INFORMATION

### Optical

Light source	Seoul Semiconductor LEDs
Lumen output	25,200 - 84,000 lumens
CRI	Ra > 70 standard; Ra > 80 & Ra > 90 optional
CCT	4000K standard; 3000K & 5000K optional
Luminaire efficacy	>140 lm/W
Beam angle	9 Distinct Optics

### Electrical

Power consumption	180W, 240W, 300W, 450W, 600W
Operating frequency	50 Hz
Operating voltage range	220 – 240V AC
Power factor	>0.9 /240V AC
Driver	MeanWell

### Environmental

IP rating	IP66
Impact rating	IK10
Net weight	9.3 kg to 21.4 kg
Ambient temperature range	-30°C to +50°C
Material composition (body)	Aluminium alloy
Material composition (diffuser)	PC Lens
Expected lifespan	>130,000 hours @L70

### Inclusions




U-bracket standard

### Warranty\*

5 years


Data subject to change without notice  
\* Refer to warranty policy

## ACCESSORIES

Part #	Order Code	Description
	add <b>BSG</b> to the model number	Back spill guard available for lens options L2, L3, L4, L5, L6
	<b>SFL-PM-S</b>	Pole mount for 180W – 300W SuperNova lights, 1 or 2 lights on pole, fits 76mm diameter round pole
	<b>SFL-PM-L</b>	Pole mount for 450W & 600W SuperNova lights, 1 light on pole, fits 76mm diameter round pole

## MOUNTING

The SuperNova™ comes with an adjustable U-bracket which is suitable for wall mounting. It can also be mounted on a pole using a customised adaptor. The tilt angle can be adjusted to comply with lighting design requirements. The electrical supply wiring can be terminated within the light.



## OPTIONAL BACK SPILL GUARD

Control the obtrusive effects of outdoor lighting through using an optional back spill guard. Direct your light where you need it, whilst eliminating unwanted light entry into neighbouring areas.

This fitting easily attaches to the LED panel and is applicable for L2, L3, L4, L5, L6 lens options.



## COMPLIANCE

The SuperNova™ LED Floodlight meets or exceeds all relevant standards and regulatory requirements.

For a full compliance and testing list visit [www.enlighten.com.au](http://www.enlighten.com.au).

IES files, warranty, installation and product guides are also available for download.

Sold nationally through major electrical wholesalers.

